



SALEM TOWNSHIP FIRE DEPARTMENT S.A. SMOKE ALARM INSTALL

Date: Requested Ins	stall Date: Time:
First name:	Last Name:
Address:	_ City:Zip:
Phone:	Email:
#ofChildren Children under 10	# of Adults # of Adults over 65 yrs. of age
Number of existing alarms Working?	Number of alarms installed #Yes #No
Alarms over 10-years Declined servi	
Notes:	
 Locations to install alarms One in every bedroom. Common areas between bedrooms (hallways, entryways, or nooks). One on every level of home including basement. Not outside bathrooms or kitchen where steam or cooking fumes could trigger alarm activation. Don't install smoke alarms near windows, doors or ducts where drafts might interfere with their operation. All alarms should be installed high on the wall (4-12 inches from ceiling) or on the ceiling (4 inches from wall). Common reasons for alarm failure Missing or disconnected battery Dead or discharged battery Lack of cleaning Defective unit Improper placement Hardwire failure or shortage Instructions on maintaining alarm Clean and test monthly. (Show & make occupant test alarm) Never paint smoke alarms. Paint, sticker, or other decorations could cause the alarms to malfunction. 	
These are key points to explain to the residents for proper cleaning and maintenance.	
Pub-ed Requested Emergency Run#	Other
Who Installed:	Date Installed: